

# AGM 12/55 (group 24)



Product code: 62000550

In AGM batteries, the electrolyte (mixture of water and sulphuric acid) is largely absorbed in glass fibre. This type of battery is entirely maintenance-free and there is no gas formation with normal use. AGM batteries can be installed anywhere.

Their construction gives a very fast discharge at very high currents so AGM batteries are ideal for systems that require high currents (for instance when starting an engine). The battery poles can be unscrewed and this type of battery can be combined with every standard battery terminal.

- Excellent starter function.
- Perfect upgrade for flooded lead acid batteries.
- Same initial power surge in an AGM 12/90 Ah as 180 Ah flooded lead-acid battery.
- Glass-fibre technology ensures low internal resistance.
- Use of thicker plates extends lifespan.
- Can be combined with every standard battery terminal.
- Also for medium cyclical use.
- Two year warranty.

# Specifications

## General specifications

Nominal battery voltage	12 V
Nominal battery capacity C20	55 Ah
Max. charge current	15.3 A
Terminals	M6 / A-type
Outside dimensions, l x w x h (incl. handles, without automotive terminal post)	257 x 132 x 200 mm 10.1 x 5.2 x 7.9 inch
Weight	17 kg 37.5 lb

## Technical specifications

CCA to DIN	250 A
CCA to SAE	400 A